

Vermeer VR1428



Specifications

Dimensions and Weights

Raking Width - Minimum: 22 ' (6.71 m)
Working Height: 6.25 ' (1.91 m)
Wing Flex Up: 36 " (91.44 cm)
Wing Flex Down: 48 " (121.92 cm)
Windrow Clearance: 18 " (45.72 cm)
Weight - Total: 5040 lbs (2286.11 kg)
Weight - Tongue: 1300 lbs (589.67 kg)
Raking Width - Maximum: 28 ' (8.53 m)
Windrow Width - Minimum: 36 " (91.44 cm)
Windrow Width - Maximum: 72 " (182.88 cm)
Transport Width: 10 ' (3.05 m)
Transport Length: 30.2 ' (9.2 m)
Transport Height: 6.25 ' (1.91 m)
Working Width: 32 ' (9.75 m)
Working Length: 26.2 ' (7.99 m)

Tractor Requirements

Horsepower: 40 hp (29.83 kw)
Hydraulics - Type: Three double acting
Hydraulic Pressure: 1800 psi (124.11 bar)
Hydraulic - Flow Rate: 5 gpm (18.93 L/min)
Hydraulic - Quantity: 2

Standard Details

Rake Style: High capacity V-rake
Rake Wheel Tooth Diameter: 0.28 " (0.71 cm)
Transport Wheels - Size: 11L-15 Intermitent highway rated
Transport Wheels - Qty: 2
Gauge Wheels - Size: 11L-15 Intermitent highway rated
Gauge Wheels - Quantity: 2
Transport Lights: Yes
Hitch Jack: Yes
Speed - Maximum: 14 mph (22.53 km/h)
Rake Wheel - Quantity: 14
Rake Wheel - Diameter: 55 " (139.7 cm)

Vermeer VR1428

Rake Wheel - Hubs: Tapered roller bearings

Rake Wheel - Teeth per Wheel: 40

Optional Features

Central Kicker: Center spiltter - two wheel

Safety Chain: Yes

Last Updated: 09/15/2011

Contains information from Vermeer Corporation operated web site. Its use is subject to terms and conditions of Vermeer Corporation operated web site agreement at <https://www2.vermeer.com>.

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation. ©2009 Vermeer Corporation. All Rights Reserved.

09/16/2011